

**MV 100 KV
MV 120 KV
MV 125 KV
Series**



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- Wall mounting.

Design

- Made of quality and durable plastic.
- Suitable for mounting with flexible air ducts.
- Equipped with deviators for back air flow prevention through the bottom ventilation grille.
- Extra ventilation grille is provided to arrange natural ventilation in premises with a gas stove.
- Screw fixing.
- The grille has a removable bottom part for easy cleaning.

Colour modifications



Modifications

MV 100 KV, MV 120 KV, MV 125 KV – models with a round flange (KV)



- Equipped with a round flange for connection to \varnothing 100 mm (MV 100 KV), \varnothing 120 mm (MV 120 KV), \varnothing 125 mm (MV 125 KV) air ducts.
- MV 100 KVs, MV 120 KVs, MV 125 Ks – models with a protecting insect screen.



Overall dimensions

Model	Dimensions, [mm]							Air pass, [m ²]
	B	H	B1	H1	D	L1	L	
MV 100 KV	182	252	160	226	100	75	10	0.0039
MV 120 KV	182	252	160	226	120	75	10	0.0039
MV 125 KV	182	252	160	226	125	75	10	0.0039

