


## DKM series



Access doors on a metal frame recessed for ceramic tiles



### Applications

- Designed for wall installation and ceramic tile attachment.
- Enable quick and convenient access to concealed equipment and utility lines.
- Concealed mounting for esthetic appearance.
- Suitable for high-humidity areas.
- Protected by national patents worldwide.

### Design



- The metal frame contains magnets for plate attachment and hides the tile-to-tile gap.

- Metal plate for attaching ceramic tiles.
- Magnetic attachment of plate to the frame.
- Press gently to open and close or use a cup plunger.
- A wide range of sizes.

### Mounting

- Easy installation using mounting foam or mortar.
- Height-adjustable magnets enable perfect leveling of tiles to the wall surface.
- Ceramic tiles are easily glued to the plate.
- Easy servicing.

### Sample Installations



### Dimensions

Model	Dimensions, mm				
	B	H	B2	H2	L
DKM 150x150	163,6	163,6	150	150	26
DKM 150x200	163,6	213,6	150	200	26
DKM 150x250	163,6	263,6	150	250	26
DKM 150x300	163,6	313,6	150	300	26
DKM 200x200	213,6	213,6	200	200	26
DKM 200x250	213,6	263,6	200	250	26
DKM 200x300	213,6	313,6	200	300	26
DKM 200x350	213,6	363,6	200	350	26
DKM 200x400	213,6	413,6	200	400	26
DKM 200x450	213,6	463,6	200	450	26
DKM 200x500	213,6	513,6	200	500	26
DKM 250x250	263,6	263,6	250	250	26
DKM 250x300	263,6	313,6	250	300	26
DKM 250x350	263,6	363,6	250	350	26
DKM 250x400	263,6	413,6	250	400	26
DKM 300x300	313,6	313,6	300	300	26
DKM 300x350	313,6	363,6	300	350	26
DKM 300x400	313,6	413,6	300	400	26
DKM 300x450	313,6	463,6	300	450	26
DKM 300x500	313,6	513,6	300	500	26
DKM 400x400	413,6	413,6	400	400	26
DKM 400x500	413,6	513,6	400	500	26
DKM 500x500	513,6	513,6	500	500	26
DKM 600x600	613,6	613,6	600	600	26