

Thermovent Flex series



Semi-flexible stainless steel air ducts with high temperature resistance

Description

Spiral seam stainless steel air ducts with high aerodynamic and strength characteristics.

Features

- Made of incombustible corrosion-resisting stainless steel band.
- Increased thermal resistance (up to 800°C).
- Specially designed high-quality locks ensure high seam tightness and total air tightness of the ducts.

- Smooth internal surface ensures low dynamic losses.
- Low weight and easy mounting.

Recommended application

- Applied in residential and industrial ventilation, air conditioning and heating systems with the maximum pressure 10 000 Pa.
- For supply and exhaust ventilation.
- Applied in the systems of hot air removal from boiler houses and smoke exhaust sys-

Technical data

ltem		Thermovent Flex
Diameter range [mm]		50/60/80/100/110/120/125/130/135/140 /150/160/180/200/250/300/350/400
Material		Stainless steel
Number of layers		2
Total thickness [µm]		100
Operating temperature range [°C]		-30+800
Maximum air speed [m/s]		30
Maximum operating pressure [Pa]		10 000
Minimum bend radius [mm]	up to Ø 200 mm	4D
	above Ø 200 mm	4,5xD
Length [m]		1; 2; 3; 6

Packing



Cardboard box

Order code

Thermovent Flex

Ø

length

Accessories

Diffusers and air disk valves











Grilles and hoods













Backdraft dampers